EU-TYPE EXAMINATION CERTIFICATE




The following model of Personal Protective Equipment has been subjected to an EU-type examination in accordance with the module B of the PPE regulation (2016/425) and has been shown to satisfy to essential health and safety requirements.

Certificate N° 0075/797/162/04/19/1314

Issued by CTC, Notified Body N°0075, to the following model of personal protective equipment :

Manufacturer :	HONEYWELL SAFETY PRODUCTS EUI Immeuble Edison ZI-Paris Nord II 33, ROISSY CDG CEDEX France		
Description	Trance		
PPE Type :	protective glove against mechanical	l risks, chemical risks,	
Product reference :	4580130		
Glove description :	5 fingers glove, Heavy natural latex, pattern, Rolled cuff	Powder free. Raised	
Available sizes :	07 - S08 - M09 - L10 - XL		
Pictures :			
	Honeywell	Address:	



Reference standard :

Levels of performance / class of protection

0110X

EN 420:2003 + A1:2009 EN 388:2016 + A1:2018

« X »indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

EN ISO 374-5:2016	MICRO-ORGANISMS
EN ISO 374-1:2016 / A1:2018	Туре С

This product is a category III (letal or irreversible risk). This certificate shall only be used in conjuncture with the conformity assessment procedure according to module C2 (VIPO 2369)

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

5

Ctas

Full description of the PPE, reference rules verified in the context of the EU-type examination and information given on the product are detailed in the manufacturer's technical file and the Instruction for Use index 02 dated from June, 2021

NOTA : Any modification to new items of the personal protective equipment object of this EU type approval certificate or any modification of the information contained in the manufacturer technical file which served for the deliverance of the EU type approval certificate (change of address, change of company status) should be brought to the attention of the notified body in accordance with Annex V §7.2 of Regulation 2016/425. Any marking on the PPE which is not concerned by the Regulation (UE) 2016/425, is not covered by this certificate.

NB 0075

Issued in Lyon by Didier GUISADO

Certification and Quality Manager

In application of the Regulation 2016/425 of the European parliament and the Council of 9th March 2016 related to Personal Protective Equipment and repealing the Directive 89/686/EEC. Date of first issue : 19 April 2019 End of validity date : 19 April 2024

Update 01 : 21 June 2021

www.ctcgroupe.com

cemarking@ctcgroupe.com

CTC - 4, rue Hermann Frenkel - 69367 Lyon cedex 07 - France ation 3 (0)4 72 76 10 10 - Fax : +33 (0)4 72 76 10 00 - ctclyon@ctcgroupe.com



MARKIN

TIFIED BODY

n° 0075

by CT

Accreditation n# 5-0594 Scope available on: Comité Professionnel de Développement Économique (CPDE) Cuir Chaussure Maroquinerie Ganterie Loi 78-654 du 22.06.1978 - Siret 77564972600160 - Code NAF 9412Z - TVA FR 88775649726

HONEYWELL SAFETY PRODUCTS EUROPE

MANUFACTURER'S TECHNICAL FILE TO THE PPE REGULATION 2016/425

Reference of the product	:	4580130
Article code	:	
Technical file index	:	02
Last update	:	June, 2021

IDENTIFICATION

Reference of the product : Article code :	:	4580130
Basic Model		
Technical file index :	:	02
Last update :	:	June, 2021

Manufacturer :

HONEYWELL SAFETY PRODUCTS EUROPE

Immeuble Edison ZI-Paris Nord II 33, Rue des Vanesses 95 958 ROISSY CDG CEDEX

France

tel: 01.49.90.79.79 fax: 01.49.90.79.80

Factory :

SafeMed Pro Ltd

Thunstrasse 29 3005 Bern

Suisse

tel: 41 31 819 24 67 fax: 41 31 819 11 54

Kossan Rubber – SafeMed Industries Bhd.

Wisma Kossan, Lot 782 - Jalan Sungai Putus, Off Batu 3 3/4 - Jalan Kapar, 42100 Malaysia tel: +603-3291 2657

fax: +603-3291 2903

GLOVE DESCRIPTION

General glove description :

5 fingers glove, Heavy natural latex, Powder free. Raised pattern, Rolled cuff

type of coating finish : smooth

Visual description (picture back and palm sides) :



Field of use

Low chemical risks, Micro-organism, Automotive and Part Manufacturer, Aviation, Catering, Chemical Industries, Food Industries, Industrial Cleaning, Laboratory, Maintenance, Medical and Pharmaceutical, Petrochemical, Printing Industries, Water treatment

	Risk assessment (Essential Health and Safety Requirement. Annex II - PPE Regulation)			
		Applicable	Covered by	
§1	Requirements defined in the Annex II §1 are applicable to all PPE	 ✓ 	 ✓ Standard ✓ Instruction for use ✓ Marking 	
§1.4	Manufacturer's instructions and information is available	7	 Standard ✓ Instruction for use Marking 	
§2.5	PPE which may be caught up during use	7	Standard Instruction for use Marking	
§2.12	PPE bearing one or more identification markings or indicators directly or indirectly relating to health and safety	7	 ✓ Standard ✓ Instruction for use ✓ Marking 	
§2.14	Multi-risk PPE	v	 ✓ Standard ✓ Instruction for use ✓ Marking 	
§3.3	The PPE is intended to protect against mechanical injuries	\	 ✓ Standard ✓ Instruction for use ✓ Marking 	
§3.10.2	PPE intended to protect against substances and mixtures which are hazardous to health and against harmful biological agents - Cutaneous contact	7	 ✓ Standard ✓ Instruction for use ✓ Marking 	

Available sizes :

Minimum length of glove (mm) / Minimum width of glove (mm)	Sizes
300/85	07 - S
300/95	08 - M
300/104	09 - L
300/113	10 - XL

Glove constitution :

	Reference	Color	Material	Surfacic mass	Gauges	Thickness
Palm	3000174	Blue	Natural Latex			0,25 mm
Back	3000174	Blue	Natural Latex			0,25 mm
Cuff	3000174	Blue	Natural Latex			0,25 mm

PROTECTION SCOPE

This glove meets the essential requirements of the Personal Protective Equipment Regulation 2016/425.

This glove is designed against mechanical risks, chemical risks, microorganisms risks and other risks.

It is a category III product, module C2

Notified Body Reference : VIPO (2369)

Gen. Svobodu 1069/4, 958 01 Partizanske, Slovakia

GENERAL REQUIREMENTS

Standard EN 420 : 2003 + A1 : 2009

Dexterity : 5 Size : conform

At the date of certificate the product is in compliance with Annex XVII of REACh regulation (n° 1907/2006 and revisions)

SPECIFIC REQUIREMENTS AND PERFORMANCE LEVELS

Mechanical hazard EN 388 : 2016 + A1 : 2018

Protection offered	Performance levels
Abrasion resistance	0
Blade cut resistance	1
Tear strength resistance	1
Puncture resistance	0
Cut Resistance method (EN ISO 13997)	Х
Impact Protection	-

The levels of performance have been measured on the palm

« X » indicates that the glove has not been submitted to the test or the test method appears not to be suitable for the glove design or material.

Chemical hazard EN 374-2 : 2014

Protection offered	Performance levels
Water tightness	conform
Air tightness	conform

Chemical hazard EN ISO 374-1 : 2016 / A1 : 2018

Tuna		Туре С
Туре	•	Type C

Tested chemical :	CAS N°	Letter	Permeation performance levels:	Degradation value:
Sodium hydroxide 40%	1310-73-2	K	6	-80,8%
Sulphuric acid 96%	7664-93-9	L	2	17,4%

Microorganism EN ISO 374-5 : 2016

This glove protect against microorganism

Uncontrolled against viruses

TEST REPORTS

Laboratory	CTC	Other
EN 420 + innocuousness	L181122709_1	
EN 388	L181122709_1	
EN 374-2	L180508982_1	
EN 16523-1	L190306288_1 L190306296_1	
Other	L180408409_1	IP1402-0440

MARKING - PACKAGING

Information printed on the glove :

Logo of Manufacturer : Logo CE Glove's reference : 4580130 Article Code : Size indicator Pictograms related to risks against which protection is offered with performance levels Information pictogram Address of Manufacturer : Date of Manufacture (month/year) and/or Serial number :

Marking example :



Method of marking on the glove :

Marking on the box

Packaging :

The carton contains 10 boxes of 50 gloves, so 500 gloves per box

PPE subject to ageing :

The design performance can not be significantly affect by ageing when stored in appropriate conditions (humidity, temperature, clean, ventilated, light).

Declaration of conformity :

Available on : https://doc.honeywellsafety.com/

MEANS OF CONTROL

Final Inspection : in accordance to ISO 2859 level 2. Major defects : NQA = 0,65 / Minor defects : NQA = 0,65.

Sampling Plan		Quantity of acceptable defects	
Lot Quantity	Sample Quantity	Minor Defects	Major Defects
110 to 200	D 8	2	0
201 to 500	F 20	5	1
501 to 1200	G 30	7	1
1201 to 10000	J 80	14	3
10000	K 125	21	5